PS236

Getac

Getac PS236Fully Rugged Handheld

MIL-STD 810G and IP67 Compliance
Microsoft Windows Mobile® 6.1
3.5G WWAN
RS232 Serial Port, USB OTG & SDIO / SDHC Slot
Field Swappable Long Life Li-lon Battery
Embedded High Sensitivity GPS Receiver
3 Megapixel Pixels Auto-focus Camera







The Getac PS236 Fully Rugged Handheld

The Getac PS236 is the first fully rugged handheld built to meet MIL-STD 810G with high-speed HSDPA wireless networking*. The PS236 features a high sensitivity GPS receiver, E-Compass and altimeter, making it perfect for GIS applications and a built-in three megapixel auto-focus camera has been neatly integrated to provide an all-in-one solution.

The PS236 includes 4GB of embedded storage and can be expanded to a total of 20GB of storage using the external SDHC card** The PS236 can be customized with either the standard

numeric keypad or a PDA keypad depending on the application and need. The PS236 is preinstalled with Windows® Mobile 6.1 software for quick access to email, the Internet, texting and other means of mobile communications.

Weighing a mere 18 ounces, the device can operate at full capacity for up to 12-hours on a fully-charged battery and is MIL-STD 810G compliant and IP67 compliant to operate without failure under the most extreme weather conditions, environments and everyday abuse associated with its user base.

Getac PS236 Specifications

ruggedsales@getac.com 949.681.2900

Getac, Inc. 43 Tesla Irvine, CA 92618

Ruggedness Water & dust resistance: IP67

Drop spec:

1.52 m (5 ft) drop on all faces, edges and corners on steel per MIL-STD-810G

Electrostatic discharge: +/- 15kVdc air discharge, +/- 8kVdc contact discharge

Tumble spec:

1,000 1.6 ft/0.5m tumbles (2,000 drops)

Genuine Windows® Mobile 6.1 Classic **Operating System**

Genuine Windows® Mobile 6.1 Professional

Microprocessor Marvell PXA310 806MHz

Memory and 128MB MDDR

> 256MB NAND Flash and 4GB iNAND* Storage

SD Card Slot SDIO and SDHC

(up to 16GB SDHC memory card*)

Display 3.5" VGA (480 x 640 pixel)

Transflective sunlight readable display

Pressure sensitive touchscreen

Soft input panel (SIP) on screen keyboard Keypad

> Transcriber handwriting recognition Optional numeric or PDA keypad

Communications WLAN 802.11 b/g

Bluetooth (v2.0 +EDR Class 2)

Camera 3 Megapixel auto-focus

Special Features E-Compass

Altimeter

Included Accessories Microsoft getting started disc

> AC adaptor USB cable Protective film Hand strap Quick start guide

Battery Sylus pen

Chipset: SiRF Star III **GPS Sensor Specifications** Receiver type: L1 (C/A)

Channels: 20 channel all-in-view tracking

Update rate: 1 Hz Autonomous: 5 m DGPS: 1~3 m

Cold start time: 45 sec average Warm start time: 30 sec average Hot start time: 1 sec average Reacquisition: 0.1 sec average

Power Battery type: 3.72V, 5600 mAh

Li-Ion battery pack

Dimensions and 7" x 3.5" x 1.18"

> Weight (178 x 89 x 30 mm)

17.64 oz (500g)**

Operating temp: **Temperature**

-22°F to 140°F (-30°C to 60°C)

Storage temp:

-40°F to 158°F (-40°C to 70°C)

Humidity: 5% ~ 95% (non-condensing)

I/O Interfaces SDIO / SDHC x 1

> DC x 1 USB OTG x 1 RS232 x 1

Office docking port x 1

Speaker x 1 Camera x 1 Battery cover x 1 Stylus pen x 1

Warranty 3 Year limited warranty standard[†]

Specification subject to change without notice. Battery performance will vary based on software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. As with all batteries, maximum capacity decreases with time and use and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings. Battery life may be reduced in subzero applications.

Copyright 2010, Getac, All Rights Reserved. Getac and the Getac logo are either registered Specification subtrademarks or trademarks of Getac Technology Corporationject to change without notice. Battery life testing conducted under in the United States and/or other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and in other countries. All other trademarks are the property of their respective owners.

^{**} Weight is without 3G module. Weight varies by configuration and manufacturing process.

[†] For warranty terms and conditions visit www.getac.com